Large Screen LED-backlit LCD

32" | 42" | 46" | 55" | 65"

NEC E SERIES

Essential performance. Enticingly priced.

LED-Backlit, Commercial-Grade LCD Displays Ideal for Education, Corporate and Digital Signage Applications

The Essentials

With a brilliant panel and simplified controls, the NEC E Series delivers everything you need for captivating digital signage

- Integrated RS-232C allows for external control of the display
- High-definition and high contrast ratio displays provide stunning images
- Built-in tuner allows for high-definition broadcast capabilities
- Additional energy options include a Power Savings Mode to further reduce energy consumption

The Extras

Delivering more than just the basics, the NEC E Series has integrated features that will leave no head unturned

- LED backlighting enables eco-friendly digital signage
- Reduced bezel width creates seamless digital signage*
- Multiple HDMI ports enhance best-in-class connectivity
- Internal, 10W down-firing stereo speakers enhance the experience with superior sound
- 3-year warranty protects your investment

*On select E Series displays

Performance-Driven Design

The Essential

Quality design and performance is expected of digital signage displays in order to attract, engage and inform audiences. With a slim, sleek bezel and a high contrast panel, NEC E Series displays are points of attraction poised to deliver brilliant content.

The Extras

The NEC E Series goes above and beyond what you've come to know as a traditional display design. With an LED edge-lit backlighting source that contributes to a reduced depth and lighter weight, these displays are mere slivers of the previous generation of displays. These benefits also make this fourth generation of E Series displays easy to transport and install.

*On select sizes

Corporate Applications

The Essential

Ideal for digital signage in corporate lobbies, and presentations, video conferencing and boardrooms, the NEC E Series provides the basics for control (RS-232C) in concert with a brilliant display.

The Extras

LED backlighting enables a thinner, sleeker display – all the better to showcase corporate messaging and enable cross-company collaboration. LED backlighting also leads to reduced total cost of ownership and, with a mercury-free design, it has a reduced environmental impact as well.

Education Applications

The Essential

With integrated speakers and a tuner, the NEC E Series is designed for implementation in educational environments. Digital signage can achieve campus-wide connectivity through a single point of access by alerting passersby of upcoming events and emergency notifications, while classroom displays provide a bright alternative to projector screens.

The Extras

The NEC E Series is perfect for schools looking to upgrade their old CRT televisions. Impress prospective students, parents and visitors with a progressive, technology-forward school environment. What's more – these displays are priced to compete, meaning even schools with the tightest of budgets can upgrade their classrooms.

Eco-friendly Features

The Essential

Environmental features are an expected consideration when it comes to digital signage and the NEC E Series is no exception. An integrated backlight adjust setting allows users to customize the backlight strength, enabling a longer display life and lower power consumption. An energy savings picture mode is built into the on-screen menu to improve energy efficiency.

The Extras

With LED backlighting, the NEC E Series is more slim and sleek than ever. Not only are LED backlights mercury-free, they contribute to reduced power consumption and therefore a lower total cost of ownership.

Specifications for E323/E424/E464/E554/E654

MODEL	E323	E424	E464	E554	E654
QUICK SPECS					
LCD MODULE					
Panel Technology	A-MVA				
Viewable Image Size	32"	42"	46"	55"	65"
Native Resolution	1360 x 768	1920 x 1080			
Brightness (Typical/Max)	350 cd/m²	360 cd/m²	350 cd/m²		
Contrast Ratio (Typical)	4000:1	1200:1	4000:1		
Viewing Angle	178° Vert., 178° Hor. (89U/89D/89L/89R) @ CR>10				
Aspect Ratio	16:9				
Active Screen Area (W x H)	27.5 x 15.4 in. / 697.7 x 392.2mm	36.9 x 20.9 in. / 938.2 x 531.3mm	40.4 x 22.9 in. / 1026.1 x 580.7mm	47.9 x 27.1 in. / 1217.2 x 687.8mm	56.3 x 31.7 in. / 1430.9 x 806mm
Orientation	Landscape				
Displayable Colors	More than 16.7 million				
CONNECTIVITY					
PC/Mac Signal Compatibility	Yes				
Input Terminals					
Digital	HDMI (3)				
Analog	VGA 15-pin D-sub, RCA (Y, Cb/Pb, Cr/Pr) Component				
Audio	RCA Audio, HDMI Audio, Audio Mini-Jack	HDMI Audio, Stereo Mini-Jack			
External Control	RS-232C				
Output Terminals					
Audio	Optical Digital Audio	SPDIF			
Audio Amplifier	10W (down-firing)				
POWER CONSUMPTION					
On (Typical)	65W	85W	100W	122W	260W
ECO Mode Standby	<0.5W				
PHYSICAL SPECIFICATIONS					
Bezel Width (L/R, T/B)	0.87 in./0.87 in., 0.87 in./1.9 in.; 22mm/22mm, 22mm/48.8mm	0.37 in./0.37 in., 0.37 in./1.3 in.; 9.5mm/9.5mm, 9.5mm/32.4mm	0.39 in./0.39 in., 0.39 in./1.3 in.; 9.9mm/9.9mm, 9.9mm/32.4mm	0.39 in./0.39 in., 0.39 in./1.3 in.; 9.9mm/9.9mm, 9.9mm/32.4mm	0.7 in./0.7 in., 0.7 in./1.9 in.; 18mm/18mm, 18mm/48mm
Net Dimensions (without stand; WxHxD)	29.3 x 18.4 x 2.3 in. / 745.2 x 466.5 x 58mm	37.7 x 22.6 x 2.5 in. / 957.6 x 574.0 x 63.5mm	41.2 x 24.5 x 2.5 in. / 1046.4 x 622.3 x 63.5mm	48.9 x 28.9 x 2.5 in. / 1242.1 x 734.1 x 63.5mm	57.7 x 34.3 x 4 in. / 1465.6 x 871.22 x 101.6mm
Net Weight (without stand)	17.6 lbs. / 8 kg	26.7 lbs. / 12.1 kg	30 lbs. / 13.6 kg	44.2 lbs. / 20.1 kg	68 lbs. / 30.9 kg
VESA Hole Configuration	200 x 100mm (4-hole)	400 x 400mm (4-hole)			
ENVIRONMENTAL CONDITIONS					
Operating Temperature	32-104°F / 0-40°C				
Operating Humidity	10 - 85%	10 - 80%			
Operating Altitude	9843 ft. / 3000m	6562 ft. / 2000m			
LIMITED WARRANTY	3 years parts and labor, including backlight*				
ADDITIONAL FEATURES	Built-in NTSC/ATSC (8-VSP, Clear QAM) analog/digital tuner; Variable picture modes (Dynamic Standard/Energy Savings/Theater/Custom); Advanced Video/ Audio Settings; Sleep Timer; Built-In closed captioning; Parental Control (V-Chip Function); Power management; USB Port				
SHIPS WITH	Power cord; VGA cable (Mini 15-pin D-sub); Wireless remote control; Batteries; CD-ROM (user manual); Stand; Thumbscrews; RS-232 adaptor				
OPTIONAL ACCESSORIES					
NEC	External Single Board Computer (TNETPC-ION); Wall Mount Kit (WMK-3257); Accessory pack for Wall Mount Kit (MIS513)				

* Warranty restrictions apply. Contact your representative for details.

Icon Key

- LED-backlit
- Built-in speakers
- Eco-friendly

For times when the remote is not available, full display controls are conveniently situated on the side of the bezel, allowing you to change channels, adjust the volume and access the on-screen display manager.

ENERGY STAR

Product specifications subject to change.
©2012 NEC Display Solutions of America, Inc.
All rights reserved.
25.NEC.80.GL.UN.124 rev. 06012013

NEC Display Solutions
500 Park Boulevard, Suite 1100
Itasca, IL 60143
866-NEC-MORE

necdisplay.com